

MP56 Pressure Transducer


100mV Output @ 5.0 Vdc, NPT Threaded Fitting

Introduction

Piezo-Metrics Model MP56 is a miniature, low cost, general use pressure transducer. These transducers are made of corrosive resistant titanium (6AL4V) and utilize high reliability semiconductor strain gages bonded directly to the inside surface of the machined diaphragm.

Pressure on the diaphragm is applied through the hole in the 1/8" NPT (-08) or 1/4" NPT (-04) fitting end which is then converted to an electric signal proportional to the pressure

The Model MP56 is available in either Gage (PSIG), Absolute (PSIA), or Sealed Reference (PSIR) pressure configurations. The Absolute and Sealed Reference configurations utilize a welded Titanium hermetic header. The hermetic header is located just behind the strain gage diaphragm section of the sensor and seals the sensitive gages in a vacuum which dramatically increases stability and reliability. Long term stability versions are available.



Applications

- Test & measurement equipment
- Production equipment & controls
- Energy Controls
- Laboratory instruments & equipment
- Liquid level
- Calibration Equipment

Performance Options *

	A	C	Units
Balance (Zero) **	0.00 ± 3.00	0.00 ± 2.00	mV
Full Scale Sensitivity	20.0 ± 2.00	20.0 ± 2.00	mV/V
Static Error Band (Best Fit Straight Line)	± 0.50	± 0.25	%FS (BFSL)
Thermal Balance (Zero) Shift	± 0.02	± 0.01	%FS/°F
Thermal Sensitivity Shift	± 0.02	± 0.01	%FS/°F

Standard Long Term Stability	± 2.00 %FS/Year Max.				
Long Term Stability Options	L10 = <1.0	L5 = <0.5	L2 = <0.2	L1 = <0.1	%FS/year

Mechanical

Pressure Ranges	50, 100, 200, 300, 500, 1k, 2k, 3k, 5k, 7k * PSI
Other ranges possible	Consult Factory
Over Pressure (No change out of spec.)	2.0x Range
Burst Pressure	6.0x Range

Electrical

Input	5.0 Volts DC or AC
Maximum Voltage	30 V for short periods
Input Resistance (Nominal)	1500 Ohms
Output Resistance (Nominal)	450 Ohms
Insulation Resistance Minimum	50 Megohms @ 50 VDC

Contact: — www.piezo-metrics.com — sales@piezo-metrics.com
 4584 Runway Street • Simi Valley, CA 93063 USA
 (805) 522-4676

Precision Metric™ and Precision Matched™ are trademarks of Piezo-Metrics, Inc.
 ©2025 Piezo-Metrics, All Rights Reserved




PIEZOMETRICS™
 Inc.



DS-MP56 Issue: 7/2025

Environmental

Storage and Operating Temperature	0° to 180°F
Compensated Temperature Range	30° to 130°F *
Other Temperature Compensated Ranges	Consult Factory
Acceleration	100g's any axis
Media Compatibility (wetted surface)	Liquids & Gases compatible with Titanium 6AL4V



* Custom Performance Options and special cable length available - Consult Factory.

** Balance (Zero) set point: Gage (PSIG) & Sealed Reference (PSIR) - (Zero) set at "0"PSIG atmospheric pressure. Absolute (PSIA) - (Zero) set at "0"PSIA pressure relative to an absolute vacuum.